




真空泵 / Vacuum Pump

型号 VP0140





空气量和消耗功率 / Airflow & Power Consumption



* 特性图只是参考值，并不是保证值。

/The characteristic charts are for reference only and are not guaranteed.

外形尺寸图 / External Dimensions (单位 / Unit : mm)



规格 / Specifications

达到真空度 * / Attainable Vacuum	-53.3 kPa (-400 mmHg) -533 mbar -15.7 in. Hg	
吐出空气量 / Free Air Displacement	3 L/min 0.106 cfm	
额定电压 / Rated Voltage	115 V AC	230 V AC
额定频率 / Rated Frequency	50 Hz / 60 Hz	
消耗功率 / Power Consumption	15 W / 14 W	
耐用时间 (MTTF) / Rated Performance (MTTF)	5,000 小时 / hours	
吸入口尺寸 / Inlet	$\phi 6$ mm (外径) 软管接头 / 6 mm O.D. hose barb	
吐出口尺寸 / Outlet	$\phi 6$ mm (外径) 软管接头 / 6 mm O.D. hose barb	
额定时间 / Duty Cycle	60 分钟	
线圈绝缘等级 / Coil Insulation Class	UL 规格品: 相当于 B 类 / Class B for UL	相当于 E 类 / Class E equivalent
安装尺寸 / Mounting Dimensions	48 (L) x 62 (W) mm 1 - 57/64" (L) x 2 - 7/16" (W)	
本体重量 / Weight	0.7 kg 1.54 Lbs	
导线长度 / Leadwire Length	200 mm 7 - 7/8"	

* 高于 -53.5 kPa 运转时需要在进气管路上加装一个放气阀或泄压阀。

/ Operations at higher than -53.5 kPa need an additional leak valve or relief valve on the inlet piping.

用途例 / Application Examples

滴落式装置 / Dripping Machine



小型印刷机 / Paper Card Dispenser

